

Main Feature:

- Image CMOS Sensor
- IR Dome Camera
- 5MP Resolution @ (2560X1920P)
- 4mm HD Lens
- 2-Warm Light LED / up to 20-30Mtr.
- Mic Inbuilt & PoE Supported
- H.264 / H.265 / H.265+ Supported



2-Dual Light
IR array WL led's



Human
Target in true color



Connectivity
Network camera



High Definition
HD Recording



Microphone
Mic In-Built in Camera



MODEL

BT-IPC-GMC5D1-A

Image Sensor	1/3 CMOS
Effective Pixels	2560(H) * 1920(V) 4MP
Minimum Illumination	0.05 Lux/F1.2(Color), 30IRE, 0lux/F1.2(B/W)
White Balance	Manual/Automatic
Gain Control (AGC)	Auto
Lens	4mm
S/N Ratio	50dB
Back Light Compensation	BLC/HLC/DWDR
Main Steam	PAL:2560x1440@12.5fps
Video Streaming	2304 ^ * 1296 1920 ^ * 1080, 1280 ^ * 720, 1 - 30fps / s
Sub Steam	704 ^ * 576, 640 ^ * 480, 640 ^ * 300, 352 ^ * 288, 1 - 30fps / s
Resolution	5MP (2560 * 1920)
ICR	Auto (ICR)/Manual
Audio Input	1 Channel
IR	IR Range of 20-30 Mtr.
OSD	OSD Supported
Operating Temperature	-30^ C sim+ 60 deg * C
Power Source	12V DC
Power Consumption	1.3W
Weatherproof Standard	IP66
Protocol	ONVIF
Coding Format	H.265, H.264

