

**Main Feature:**

- Image CMOS Sensor
- IR Dome Camera
- 4MP Resolution @ (2560X1440P)
- 4mm HD Lens
- 2-Warm Light LED / up to 20-30Mtr.
- Mic Inbuilt & PoE Supported
- H.264 / H.265 / H.265+ Supported


**2-Dual Light**  
 IR array WL led's

**Human**  
 Target in true color

**Connectivity**  
 Network camera

**High Definition**  
 HD Recording

**Microphone**  
 Mic In-Built in Camera

**MODEL**
**BT-IPC-RMC4B3-A**

|                         |   |
|-------------------------|---|
| Image Sensor            | 1/3 CMOS  |
| Effective Pixels        | 2560(H) * 1440(V) 4MP   |
| Minimum Illumination    | 0.05 Lux/F1.2(Color), 30IRE, 0lux/F1.2(B/W)                       |
| White Balance           | Manual/Automatic  |
| Gain Control (AGC)      | Auto  |
| Lens                    | 4mm   |
| S/N Ratio               | 50dB  |
| Back Light Compensation | BLC/HLC/DWDR  |
| Main Steam              | PAL:2560x1440@12.5fps   |
| Video Streaming         | 2304 ^ * 1296 1920 ^ * 1080, 1280 ^ * 720, 1 - 30fps / s          |
| Sub Steam               | 704 ^ * 576, 640 ^ * 480, 640 ^ * 300, 352 ^ * 288, 1 - 30fps / s |
| Resolution              | 4MP (2560 * 1440)   |
| ICR                     | Auto (ICR)/Manual   |
| Audio Input             | 1 Channel   |
| IR                      | IR Range of 20-30 Mtr.  |
| OSD                     | OSD Supported   |
| Operating Temperature   | -30^ C sim+ 60 deg * C  |
| Power Source            | 12V DC  |
| Power Consumption       | 1.3W  |
| Weatherproof Standard   | IP66  |
| Protocol                | ONVIF   |
| Coding Format           | H.265, H.264  |

