

## Main Feature:

- 4MP (2560 x 1440) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Horizontal Rotation:270°, Vertical Rotation: 90°
- Support 10x Combined Zoom
- Smart Human Detection, Motion Detection, Smart Motion Tracking
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compatible with all ONVIF Supported NVRs
- QR Code Scanning for Network Connection
- Monitoring: Mobile/PC Software IP PRO
- IP66 Waterproof Rating
- 4000 Lightning Protection.
- Alexa Support



ALL Network



Compression



3MP



Plug &amp; Play



Two-way intercom



Pan/Tilt



Dual Light Vision



SD Card

## MODEL

## BT-B304GPT

Image Sensor	1.3" CMOS Sensor
Resolutions	4MP (2560 x 1440)
Lens	4MMm (F2.0) & 12mm (F2.0)
IR LED	12 Array
IR Distance	30 Meters
White LED	12 White Array
White LED Distance	20 Meters
Video Compression Standard	H.264/H.265/H.265+
Video Streaming	Main Stream: 2560x1440@15 fps   Sub Stream: 800x448@15 fps
Audio Input/Output	Two way audio, Built in microphone and speakers
Audio Compression Standard	AAC/G711A
Min Illumination	Color: 0.01 Lux,Black & White: 0.001 Lux
Day & Night	IR-cut Auto ICR
Light Mode	Full Color / Infrared / Intelligent
Pan-Tilt Angle	Pan: 0° - 270°, Tilt: 0° - 90° Horizontal speed 20°/S, Vertical Speed 10°/S
Zoom	10x Combined
DNR	3D Digital Noise Reduction
On Screen Display (OSD)	Date, Time, & Title
White Balance	Auto
WDR	D-WDR
Mirror/Flip	On / Off



Electronic Shutter	Auto
AI Features	Motion Detection, Human Detection, Smart Motion Tracking.
Privacy Zone	Support 4 Zone
Monitoring	Andriod, iOS, Windows (EseeCloud/IP Pro)
Connection Mode	4G Sim Network & Lan Network
4G Frequency Band	FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Connectors	RJ45 LAN connector (100 Mbps) and DC Power Input
Protocol	N1/Onvif
Slots	4G Sim Card / Micro SD Card
Storage	Support Micro SD Card upto 256GB & Cloud Storage (Optional)
Button	Reset Button
Light Mode Indication	LED Blink: Not connected to Network, LED Continuous ON: Connected to Network
Power Input	DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	≤15W
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic (IP66)
Dimension	148.19mm X114.98mm X 178.69mm (H x W x L)
Net Weight	580 Gms
Gross Weight	800 Gms



स्वदेशी अपनाओ, देश बनाओ  
 एक कदम राष्ट्र निर्माण की ओर...

DOWNLOAD APP



IP PRO

